

1. litre Variable Speed Refrigerated Multiple rotor Centrifuge K220R. Brushless drive



- LED display of Speed & Time
- Digital control of parameters
- Automatic soft start
- Ten Acceleration & Deceleration rates
- Ten Memory / Preset Program
- 1-90 second Pulse (Quick spin)
- CE Marked (see safety features)
- Sensors Tacho, Imbalance & Lid
- Stainless steel bowl & barrier ring



Speed 1000-15000 Rpm **Max Rcf** 22000G **Timer** 0-90mins **Size** 31x40x63Cm **Weight** 49Kg
Temperature —y to +4U U FID controlled

1. litre Variable Speed Large Multiple rotor Centrifuge K220. Brushless drive

- LED display of Speed & Time
- Digital control of parameters
- Automatic soft start
- Ten Acceleration & Deceleration rates
- Ten Memory / Preset Program
- 1-90 second Pulse (Quick spin)
- CE Marked (see safety features)
- Sensors Tacho, Imbalance & Lid



- Stainless steel bowl & barrier ring

Speed 1000-15000 Rpm **Max Rcf** 22000G **Timer** 0-90mins **Size** 29x40x48Cm **Weight** 26.5Kg



K220R. & K220. Rotors



5431
24 x 15ml fixed angle rotor
Max Speed 6000 Rpm Rcf 4800 G



5434
8 x 50ml fixed angle rotor
Max Speed 6000 Rpm Rcf 4800 G



5530
Microtiter plate rotor 4 place **Max Speed**
2000 Rpm Rcf 1500 G



5551
Swing out rotor
Max Speed 3800 Rpm Rcf 2600 G **Max capacity** 1
Litre - without adaptors a 250ml bottle can be used

Adaptors for 5551 (set of 4) Capacity below per bucket

Part Nos	5519	5521	5522	5523	5524	5525
Description	Sealed lids	100ml	50ml	4-7ml vacut	5ml	5/6ml
Nos/bucket	1	1	2	9	14	12
Tube size	n/a	45x100mm	33x105mm	11.5x100mm	13x100mm	14x100mm

Part Nos	5526	5527	5528	5529	552F	5522U
Description	10ml	12ml	15ml	20ml	15ml Falcon	27ml Universal
Nos/bucket	8	4	9	4	4	3
Tube size	16.5x108mm	17.5 x 100mm	17x100mm	33x105mm	17x120mm	13x100mm

Adaptors available for smaller tube sizes

5404 rotor	8004/8 0.5ml Tube size 40 x 8mm Max	8004/6 0.2-0.4ml tube size 40 x 6mm Max
5431 rotor	8009 10ml Tube size 110 x 12mm Max	8009S 5ml tube size 75 x 12mm Max
5434 rotor	6007 15ml Tube size 120 x 17mm Max	6006 15ml tube size 120 x 26mm Max



5404
24 x 2ml rotor
Max Speed 15000 Rpm Rcf 22000 G



8004/6 & 8
Adaptors for 0.5ml & 0.4ml



5436
36 x 0.5ml fixed angle rotor
Max Speed 15000 Rpm Rcf 22000 G



5448
48 x 0.2-0.4ml fixed angle rotor **Max**
Speed 15000 Rpm Rcf 22000 G

